



INDUSTRIAL & MECHANICAL SOLUTIONS

AVT™ EZ VALVE®



**Advanced Valve
Technologies**

www.AVTFittings.com

Sales@AVTFittings.com

AVT EZ VALVE - INSERTION VALVE

The AVT EZ Valve insertion valve can be installed on a live line with no need to shut off the water meaning it is ideal for use in industrial and mechanical applications where shutting off the flow is simply not an option.

The valve uses an integrated isolation gate, which when operated after a slot has been milled across the pipe, allows the EM (end milling) machine to be removed and the bonnet with resilient wedge to be installed.

The valve has already proved its value in a number of refineries, process plants and commercial & industrial buildings by creating control points which allow vital repair and maintenance work to be carried out.

Available in sizes 1.5" to 12" the AVT EZ Valve is durable and reliable.



BENEFITS & VALUES:

- No high-profile tapping equipment required
- No system shutoff required during installation
- No service interruption
- No risk of plugging the line with a cut coupon
- No loss of pipe integrity
- Four times quicker to install than other valves on the market - just 1 to 2 hours depending on size
- Only one excavation required for water line repair
- No concerns regarding ice plugs not holding when freezing pipes

APPLICATIONS:

- Refining and petrochemical plants
- Offshore/onshore applications
- Industrial water systems
- Booster pump isolation
- Commercial buildings
- Hospitals
- High-rise buildings
- Multiple occupancy buildings
- Make-up water
- Ground storage tank isolation
- Chilled H2O
- Fire suppression lines
- Hot and warm water pipelines



FEATURES

DESIGN

- Unique, patented technology
- Low profile design
- Ductile iron castings
- Patented gaskets which conform to irregular pipe geometries and sizes
- Size 1.5" to 12"

INSTALLATION

- Can be installed on all common pipe materials
- Installs at any angle
- Integrated isolation valve means the valve bonnet can be removed after a repair or remain in place as a permanent functioning valve
- Customizable for special applications

SAFETY

- Approved Epoxy Resin Coating
- Stainless steel Restraining Bolts for secure positioning
- 1.5 and 2": Working pressure of 100 PSI, (7 Bar)
- 3" and above: Working pressure of 250 PSI, (17 Bar) - Tested Pressure to 375 PSI (26 Bar)
- For non-water applications all sizes rated to 30 PSI (2 Bar)
- EZ Valve Components are WRAS Certified, meet UL Classified to NSF/ANSI Standard 61, Drinking Water System Components -Health Effects and AWWA C-509-01/C515-15 standards

INSTALL PROCESS



1

Prepare Insertion Site

Prepare insertion site by lubricating the gasket and contact areas



2

Lubricate Gasket Sets & Channels

Lubricate gasket sets and gasket channels in casting bodies



3

Assemble Ductile Iron Castings


Assemble ductile iron castings with ductile iron fasteners to accept a pressure test and temporarily allow rotation for milling



4

Attach EM Machine

Check integral isolation gate is fully open, fit rotation assembly, attach EM machine and apply pressure tests



5

Mill A Slot Over a 120° Path


Maintaining system line pressure, mill a slot over a 120° path
(Note: The slot normally is cut to provide for vertical valve alignment, but the installer can select any position.)



6

Retract The Milling Head

Retract the milling head, close the integral isolation gate. Replace the EM Machine with the resilient wedge bonnet, remove the rotation assembly and tighten casting fasteners to specified torque values



7

Open and Operate

Open the integral isolation gate and operate the AVT EZ Valve. For line stop applications, replace the valve bonnet with a blind flange using the integral isolation gate

CUT AWAY VALVE WITH KEY

Wrench Nut

Standard number of turns to open and close valve

Removable Valve Bonnet

Resilient wedge gate and actuation mechanism are contained for fast and easy installation or removal

Resilient Wedge

A wedge gate over a ductile iron frame that effectively seals even tuberculated host pipe

Gasket & Channel

Maintain system pressure while allowing rotation of casting assembly during slot-milling

Integrated isolation valve

Provides "under pressure" installation or removal of valve bonnets or blind flanges

Restraining Bolts

Stainless steel components secure casting assembly and provide final positioning on pipe

Insertion Slot


One narrow slot over a 120° path maintains pipe integrity and creates resilient wedge access

Pipeline Compatibility

The EZ Valve design works with most metallic pipes, AC and PVC materials

Castings

Ductile iron castings are precision machined to fit project specifications and pipe material



TEXAS

2500 E T.C. Jester
Suite 500
Houston, TX 77008
P: +1 281 590 8491

ILLINOIS

800 Busse Road
Elk Grove Village, IL 60007 P:
+1 847 364 3700
F: +1 847 364 8883



Advanced Valve Technologies

Advanced Valve Technologies (AVT) is part of ClockSpring|NRI, the high-performance critical infrastructure solutions company. AVT's advanced solutions are based on simple designs that minimize risk to the environment and reduce costly downtime. Our primary focus is on disruptions in water service that cost providers money and leave end users without service.

EZ Valve® is a registered trademark of Advanced Valve Technologies LLC.
© 2020 Advanced Valves Technologies, LLC. All rights reserved.

V: 09.21.2020

www.AVTFittings.com

Sales@AVTFittings.com