



Section 1. Identification

Product Name: DiamondWrap[®] Ultra High Temperature[™] (UHT[™]) Prepreg
Supplier: CSNRI | 621 Lockhaven Drive. Houston, TX 77073 | +1 281.590.8491
Emergency Phone Number: 800.424.9300 (CHEMTREC)
 +1 703.741.5970 (Outside the US)
Product Description: Carbon fabric impregnated with resin
Product Use: Reinforcement for pipe repair

Section 2. Hazard Identification

Classification of the substance or mixture

Acute toxicity, oral – Category 4
 Acute toxicity, inhalation – Category 4
 Skin Irritation – Category 2
 Eye Damage – Category 1
 Specific Target Organ Toxicity (Single Exposure) – Category 3
 Toxic to reproduction – Category 2
 Specific Target Organ Toxicity (Repeated Exposure) – Category 2
 Hazardous to the aquatic environment (Acute) – Category 1
 Hazardous to the Aquatic Environment (Chronic) – Category 1

Hazard pictograms:



Signal word: Danger

Hazard statements:

H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects

Precautionary statements:

P260 Do not breathe breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves, clothing, and eye/face protection.
 P301+P330 +P312 IF SWALLOWED: Rinse mouth. POISON CENTER or doctor/physician if you feel unwell.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305+P351+P338+P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P391 Collect spillage.

P403+P233 Store in well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents and containers in accordance with local, regional and international regulations.

Other hazards: N/A

Section 3. Composition/ Information on Ingredients

Substances: Not applicable

Mixture:

Component	CAS #	% Composition
Carbon fiber	7440-44-0	50 – 70
Polyphenol Cyanate Resin	87397-54-4	24 – 35
4,4'-Ethylidenediphenyl Dicyanate	47073-92-7	6 – 12
4,4'-Bis(o-propenyl-phenoxy)-benzophenone	109423-33-8	0.4 – 4
Dinonylphenol	1323-65-5	< 0.6
Nonylphenol	84852-15-3	< 0.4

Section 4. First Aid Measures

Description of first-aid measures:

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

Skin: Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. Consult a physician.

Eyes: Immediately flush eyes with plenty of clean water for an extended time, for at least fifteen (15) minutes. Remove contact lenses, if present and easy to do. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. Get medical attention immediately.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water and drink afterwards plenty of water. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed: Irritation. Pre-existing skin problems may be aggravated by prolonged or repeated contact. Persons with sensitive airways (e.g., asthmatics) may react to vapors. See section 11 for additional information.

Indication of any immediate medical attention and special treatment needed, if necessary: Treat symptomatically.

Section 5. Fire Fighting Measures

Suitable extinguishing media: Use water spray, foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media: None known.

**Specific hazards arising from the chemical:**

Unusual fire & explosion hazards: Heating or fire can release toxic gas. Closed container may rupture (due to build up in pressure) when exposed to extreme heat.

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See Section 10 Hazardous decomposition products for additional information.

Special protective actions for fire-fighters: Wear self-contained breathing apparatus (SCBA) equipped with a full-face piece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations. See section 9 for additional information.

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Keep unnecessary personnel away from spill/leak. See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Eliminate ignition sources. Personal Protective Equipment must be worn.

Environmental precautions: Do not flush product into public sewer, water systems or surface waters.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse.

Section 7. Handling and Storage

Precautions for safe handling: As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Use under well-ventilated conditions. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

Conditions for safe storage, including any incompatibilities: Keep away from heat, sparks and open flames. Do not store in direct sunlight. For ideal shelf life, store at 2-8°C in a dry, well-ventilated place. It can be stored at ambient temperatures (75 °F) for a maximum of 6 months without compromising the properties of the material. Do not expose to temperatures above 110 °F. These installation instructions are intended as a guide for standard products. Consult your representative for specific projects or unique applications. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container tightly closed when not in use. Empty container contains residual product which may exhibit hazards of product. Do not reuse empty container without commercial cleaning or reconditioning.

Section 8. Exposure Controls / Personal Protection

Control parameters:

Component	OSHA	ACGIH
Carbon fiber	2.0 ppm (mg/m ³)	10.0 ppm (mg/m ³)

Appropriate engineering controls: Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain air concentrations below occupational exposure standards. When necessary use mechanical handling to reduce human contact with materials.

Individual protection measures:

Eye protection: Full face shield with safety glasses or tightly fitting splash-proof chemical goggles.



Skin and body protection: Wear chemical resistant (impervious) gloves; PVC, neoprene, nitrile rubber, EVAL, butyl rubber. Wear chemical resistant protective clothing. Use good laboratory/ workplace procedures including personal protective clothing: lab coat and protective gloves.

Respiratory protection: Wear an approved respirator (e.g., an organic vapor respirator, a full face air purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever when performing operations involving potential exposure to aerosol, mist, spray, fume or vapor of the product.

Hand protection: Wear gloves. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of gloves are dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

Other information: Eyewash fountains and safety showers are recommended in the work area.

Section 9. Physical and Chemical Properties

Physical state:	Solid.
Color:	Black prepreg
Odor:	Sweet
Odor threshold:	No data available
Melting point:	No data available
Freezing point:	No data available
Boiling point:	No data available
Flammability (solid, gas):	Not applicable
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	No data available
Viscosity, kinematic:	No data available
Viscosity:	40,000 cP (at 77 °F) – resin
Solubility:	Negligible
Vapor pressure:	No data available
Relative Density:	10.2 lbs/gal at 75 °F – resin
Relative vapor density:	Heavier than air
Relative evaporation rate (butyl acetate=1):	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available
Explosive limits:	No data available

Section 10. Stability and Reactivity

Reactivity: For uncured material, exothermic reactions including polymerization may occur in contact with strong acids, strong bases, alkalis, amines, water, transitional metal compounds and excessive heat.

Chemical stability: This product is stable under normal conditions.

Possibility of hazardous reactions: For uncured material, exothermic reactions including polymerization may occur in contact with strong acids, strong bases, alkalis, amines, water, transitional metal compounds and excessive heat.

Conditions to avoid: Incompatible materials.

Incompatible materials: Strong acids, strong bases, alkalis, amines, water and transitional metal compounds for uncured material.

Hazardous decomposition products: Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, aldehydes, oxides of nitrogen, phenol and other products of incomplete combustion.



Section 11. Toxicological Information

Information on the likely routes of exposure: Eyes, skin, inhalation and ingestion.

Symptoms related to the physical, chemical and toxicological characteristics:

Eyes: Causes serious eye damage.

Skin: Causes skin irritation. May cause an allergic skin reaction. Harmful if absorbed through skin. Repeated or prolonged contact may cause skin irritation and dermatitis.

Inhalation: Harmful if inhaled. May cause respiratory irritation.

Ingestion: Harmful if swallowed.

Acute Toxicity:

Component	LD ₅₀ Oral (rat)	LD ₅₀ Dermal (rabbit)
Polyphenol Cyanate Resin	>2,000 mg/kg	>2,000 mg/kg
4,4'-Ethylidenediphenyl Dicyanate	500-1,000, mg/kg	N/A
Nonylphenol	1,300 mg/kg	N/A

Delayed and immediate effects and chronic effects from short- and long-term exposure: Further information is not available.

Chronic Toxicity:

Germ cell mutagenicity: Information is not available.

Carcinogenicity: Information is not available.

Reproductive toxicity: Information is not available.

STOT - Single exposure: Specific Target Organ Toxicity, Single Exposure – Category 3. May cause respiratory irritation.

STOT- Repeated exposure: Specific Target Organ Toxicity, Repeated Exposure – Category 2. May cause damage to organs.

Aspiration hazard: Information is not available.

Other information: None

Section 12. Ecological Information

Toxicity:

Component	Test	Species	Result
Polyphenol Cyanate Resin	LC50 (96 hrs)	Rainbow Trout	0.76 mg/L
	EC50 (48 hrs)	Daphnia magna	15.5 mg/L
	EC50 (3 hrs)	Activated sludge	>100 mg/L
4,4'-Ethylidenediphenyl Dicyanate	EC50 (48 hrs)	Daphnia magna	1.911 mg/L
	EbC50 (72 hrs)	Algae	0.65 mg/L
	ErC50 (72 hrs)	Algae	>1.10 mg/L est.
Dinonylphenol	EC50 (24 hrs)	Daphnia magna	0.5 mg/L
	LC50 (24 hrs)	Fish	2.725 mg/L
	ErC50 (72 hrs)	Fish	1.3668mg/L est.
Nonylphenol	NOEC (96 hrs)	Fathead Minnow	0.083 mg/L
	LOEC (96 hrs)	Lepomis Macrochirus	0.211 mg/L
	LC50 (96 hrs)	Lepomis Macrochirus	0.135mg/L

Persistence and degradability:

Component	Test	Period	Result
Polyphenol Cyanate Resin	OECD 301B	28 days	Ca. 10%



4,4'-Ethylenediphenyl Dicyanate	OECD 301D	28 days	15%
---------------------------------	-----------	---------	-----

Bioaccumulative potential: No additional information available.

Mobility in soil: No additional information available.

Other adverse effects: No additional information available.

Section 13. Disposal Considerations

Waste treatment methods: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse. Avoid release to the environment. Do not flush to sewer, watershed, or waterway.

Section 14. Transport Information

DOT / TDG / ADR / RID / IMDG / IATA / ICAO:

U.N. number: UN 1759.
Proper Shipping Name: Corrosive solid, n.o.s. (Carbon fiber impregnated with 4,4'-Ethylenediphenyl Dicyanate)
Technical shipping name: Prepreg epoxy resin.
Hazard class: Class 8
Packing group: III
Environmental hazards: Yes

Section 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

U.S. Superfund Amendments and Reauthorization Act (SARA) – SARA Section 313: Nonylphenol (CAS 84852-15-3)
 EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV – List of substances subject to authorization, Substances of very high concern: None of the components are listed.

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Nonylphenol (CAS 84852-15-3)

OTHER REGULATIONS: Additional information is not available

Section 16. Other Information

Abbreviations and acronyms used:

CAS: Chemical Abstracts Service
 DOT: Department of Transportation
 GHS: Globally Harmonized System
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 OSHA: Occupational Safety and Health Administration
 PVC: Polyvinyl Chloride
 RCRA: Resource Conservation and Recovery Act



The information contained herein is based on the data available to us and is believed to be accurate. The data is offered in good faith as typical values and not as product specification. The information in this data sheet was compiled from information supplied by the vendors of the components of this compound. CSNRI makes no warranty either expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The recommended industrial hygiene and safe handling procedures are believed to be genuinely applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. CSNRI assumes no responsibility for injury from the use of the product described herein. The information is intended only to assist in the safe handling of this material. CSNRI DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR FREEDOM FROM PATENT INFRINGEMENT. CSNRI WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Date of issue: 06/30/2020

Revision date: 06/30/2020

Supersedes: Original

Version: 1.0