

CS-205 PART B

Section 1. Product and Company Identification

Product Name:	CS-205 Part B
Supplier:	CSNRI 621 Lockhaven Drive. Houston, TX 77073 +1 281.590.8491
Emergency Phone Number:	800.424.9300 (CHEMTREC) +1 703.741.5970 (Outside the US)
Product Description:	Hardener for epoxy resin
Product Use:	Intended to repair pipes

Section 2. Hazards Identification

GHS Classification of the substance or mixture

Acute Toxicity / Oral – Category 4 Acute Toxicity / Dermal – Category 4 Skin Corrosion/Irritation – Category 1B Eye damage/eye irritation – Category 2A Specific target organ toxicity (repeated exposure) – Category 2 Aquatic hazard (Acute) – Category 1 Aquatic hazard (Chronic) – Category 1

GHS label elements, including precautionary statements Pictogram:



Signal word: Danger Hazard statements:

H302 Harmful if swallowed.

H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation

H373 May cause damage to organs (pancreas) through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects

Precautionary statements:

P264 Wash hands and skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



CS-205 PART B

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations. **Other hazards:** Warning. May be a health hazard in confined spaces.

Section 3. Composition/Information on Ingredients

Mixture:

Chemical Name	CAS No.	% by Weight
Diethylmethylbenzenediamine	68479-98-1	30 - 60
1,2-diaminocyclohexane	694-83-7	30 - 60

Section 4. First Aid Measures

First Aid Measures for Accidental:

Inhalation: Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air. If experiencing respiratory symptoms (e.g. coughing, shortness of breath, wheezing), call a Poison Centre or doctor. Immediately call a Poison Centre or doctor.

Skin contact: Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. If skin irritation occurs get medical advice/attention.

Eye contact: Avoid direct contact. Wear chemical protective gloves if necessary. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice/attention.

Ingestion: Rinse mouth with water. Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Get medical advice/attention if you feel unwell or are concerned.

Most important symptoms and effects, both acute and delayed:

Skin contact: May cause moderate to severe irritation.

Eyes contact: May cause moderate to severe irritation. May cause sensitization by skin contact.

Immediate medical attention and special treatment:

Target organs: Lungs, respiratory system, skin.

Medical conditions aggravated by exposure: None known.

Section 5. Fire-fighting Measures

Suitable extinguishing media: Use water to keep non-leaking, fire-exposed containers cool.

Unsuitable extinguishing media: None known.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA). A full-body encapsulating chemical protective suit with positive pressure SCBA may be necessary.



CS-205 PART B

Specific hazards arising from the chemical: Heating increases the release of toxic vapor. In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide; corrosive, oxidizing nitrogen oxides.

Section 6. Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures: Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental precautions: Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Methods and materials for containment and cleaning up: Small spills or leaks: stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal. Large spills or leaks: dike spilled product to prevent runoff. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal.

Section 7. Handling and Storage

Precautions for safe handling: Do not breathe in this product. Prevent all skin contact. Do not get in eyes. Only use where there is adequate ventilation. Immediately report leaks, spills or failures of the safety equipment (e.g. ventilation system). If product is transferred to another container, ensure new container is suitable for the product. Wear personal protective equipment to avoid direct contact with this chemical. Do NOT eat, drink or store food in work areas. Remove contaminated clothing and protective equipment before entering eating areas or leaving work area. Wash hands thoroughly after handling this material.

Conditions for safe storage: Store in an area that is: ventilated. Store in corrosive resistant container with a resistant inner liner. Empty containers may contain hazardous residue. Store separately. Keep closed. Follow all precautions given on this safety data sheet Comply with all applicable health and safety regulations, fire and building codes.

Section 8. Exposure Controls/Personal Protection

Exposure Limits: No exposure limit noted for the ingredients.

Appropriate engineering controls: In a confined space: general ventilation is usually adequate. For large scale use of this product: do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Provide eyewash and safety shower if contact or splash hazard exists.

Personal Protective Equipment:

Eye/face protection: Wear chemical safety goggles.

Skin protection: Wear chemical protective clothing e.g. gloves, aprons, boots. Butyl rubber, neoprene rubber, nitrile rubber.

Respiratory protection: Wear a NIOSH approved air-purifying respirator with an organic vapor cartridge if using in an unventilated area.

Section 9. Physical and Chemical Properties

Physical Appearance:	Brown liquid
Odor:	Ammonia like



CS-205 PART B

pH:	> 10			
Flash Point:	75 °C (167 °F)			
Melting Point Range:	No data available			
Boiling point:	> 191 °C (376 °F) (1,2-diaminocyclohexane)			
Evaporation rate (ether=1):	No data available			
Flammability (solid, gas):	No data available			
Specific Gravity:	No data available			
Viscosity:	No data available			
Water Solubility:	Moderately soluble (1-10%) in water			
Solubility in other solvents:	No data available			
Vapor Pressure:	No data available			
Vapor density (Air=1)	No data available			
Relative Density:	0.94 (estimated)			
Partition coefficient (n-octanol/water): No data available				
Auto-ignition Temperature:	No data available			
Decomposition Temperature:	No data available			
Explosive Properties:	No information available			
Oxidizing Properties:	No information available			
VOC Content (%):	No information available			
Flammability Limits in Air:	No data available			

Section 10. Stability and Reactivity

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Normally stable.

Possibility of hazardous reactions: None expected under normal conditions of storage and use. **Conditions to avoid:** Open flames, sparks, static discharge, heat and other ignition sources. **Incompatible materials:** Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid). **Hazardous decomposition products:** Ammonia.

Section 11. Toxicological Information

Acute Toxicity:

Likely Routes of Exposure: Inhalation; skin contact; eye contact.

Ingestion: Severely irritating to the respiratory system harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage. May cause burns to mouth, throat and stomach. **Skin contact:** Corrosive to the skin. Causes burns.

Eyes contact: Corrosive to the eyes. Causes burns.

Numerical Measure of Toxicity:

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Diethylmethylbenzenediamine	-	~ 472 mg/kg (rat)	-
1,2-diaminocyclohexane	-	~ 4556 mg/kg (rat)	-

Skin corrosion/irritation: Animal tests show moderate or severe irritation. Serious eye damage/irritation: Causes serious eye irritation based on skin irritation information. STOT (Specific Target Organ Toxicity) - single exposure



CS-205 PART B

Inhalation: Symptoms may include coughing, shortness of breath, difficult breathing and tightness in the chest.

Skin Absorption: Corrosive to skin. Causes burns. May cause sensitization by skin contact **Ingestion:** Harmful if swallowed. May cause burns to mouth throat and stomach. **Aspiration Hazard:** Can cause lung damage if aspirated based on human experience.

STOT (Specific Target Organ Toxicity) - repeated exposure: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Respiratory and/or skin sensitization: In sensitized people, exposure to a very small amount of product can cause symptoms including wheezing, difficult breathing, sneezing and runny or blocked nose. Can cause death. Symptoms can develop immediately following exposure or hours later. Repeated exposure will make the reaction worse.

Carcinogenicity: Not known to cause cancer

Key to Abbreviations

A5 = Not suspected as a human carcinogen.

Reproductive toxicity:

Development of offspring: Not known to harm the unborn child.

Sexual function and fertility: Not known to cause effects on sexual function or fertility.

Effects on or via lactation: Not known to cause effects on or via lactation.

Germ cell mutagenicity: Not known to be a mutagen.

Interactive effects: No information was located.

Section 12. Ecological Information

Ecotoxicity Effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Not readily biodegradable. This product shows a low bioaccumulation potential.

Persistence and degradability: Does not degrade rapidly based on quantitative tests.

Bioaccumulative potential: This product and its degradation products not expected to bioaccumulate based on the n-octanol/water partition coefficient (Log Kow).

Mobility in soil: No information was located.

Other adverse effects: There is no information available.

Section 13. Disposal Considerations

Waste disposal method: This product and its container must be disposed of as hazardous waste. Do NOT dump into any sewers, on the ground.

Uncleaned packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of in accordance to all local, state, national and/or international legislation/regulations.

Section 14. Transport Information

<u>Canadian TDG</u> Proper Shipping Name: Polyamine, liquid, corrosive, n.o.s. (Alkyl Polyamine) UN-Number: UN2735 Hazard Class: 8 Packing Group: III



CS-205 PART B

<u>U.S. DOT</u> Proper Shipping Name: Polyamine, liquid, corrosive, n.o.s. (Alkyl Polyamine) UN-Number: UN2735 Hazard Class: 8 Packing Group: III

IMO (Marine) Proper Shipping Name: Polyamine, liquid, corrosive, n.o.s. (Alkyl Polyamine) UN-Number: UN2735 Hazard Class: 8 Packing Group: III

Special precautions for user: Not applicable Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Section 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

Canada: WHMIS Classification



Class D2B Class E

Iass E

D2B - Toxic (Skin irritant; Eye irritant; Skin sensitization); E - Corrosive This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

USA:

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.

Section 16. Other Information

NFPA hazard ratings: Health hazard: 3 Flammability: 1 Instability: 0

Key Legend Information:

N/A – Not Applicable ND – Not Determined OSHA – Occupational Safety and Health Administration NIOSH – National Institute for Occupational Safety and Health



CS-205 PART B

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The information contained herein is based on the data available to us and is believed to be accurate. The data is offered in good faith as typical values and not as product specification. The information in this data sheet was compiled from information supplied by the vendors of the components of this compound. CSNRI makes no warranty either expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The recommended industrial hygiene and safe handling procedures are believed to be genuinely applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. CSNRI assumes no responsibility for injury from the use of the product described herein. The information is intended only to assist in the safe handling of this material. CSNRI DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR FREEDOM FROM PATENT INFRINGEMENT. CSNRI WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Date of issue: 08/08/2011

Revision date: 12/17/2019

Supersedes: 04/04/2019

Version: 3.0