

CONTOUR APEX PART A FILLER

Section 1. Product and Company Identification

Product Name: Contour Apex Part A Filler

Supplier: CSNRI | 621 Lockhaven Drive. Houston, TX 77073 | +1 281.590.8491

Emergency Phone Number: 800.424.9300 (CHEMTREC)

+1 703.741.5970 (Outside the US)

Product Description: Epoxy solution

Product Use: Intended to repair pipes

Chemical Name or Synonym: N/A

Section 2. Hazards Identification

Classification of the substance or mixture:

Skin corrosion/irritation – Category 2
Eye damage/eye irritation – Category 2A
Skin sensitization - Category 1
STOT (SE) – Category 2
Chronic Aquatic Toxicity – Category 2

Label Elements:



Hazard Statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction

H320 Causes eye irritation

H371 May cause damage to organs.

H411 Toxic to aquatic life with long lasting effects

Signal Word: Warning Precautionary Statement:

P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection

P362 - Take off contaminated clothing and wash before reuse

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water P308+P311 If exposed or concern: Call a Poison Center / doctor.

P273 - Avoid release to the environment

Section 3. Composition/Information on Ingredients

Chemical Name	CAS-No	Weight %
Phenol-formaldehyde polymer, glycidyl ether	28064-14-4	40 – 60
Bisphenol A/epichlorohydrin epoxy resin	25068-38-6	45 – 65
Propane 2,2 bis[p-2,3 epoxypropoxy)phenyl]-	25085-99-8	< 3



CONTOUR APEX PART A FILLER

polymers		
Calcium metasilicate	13983-17-0	< 20

Section 4. **First Aid Measures**

First Aid Measures for Accidental:

Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing. Wipe excess from skin. Lather with waterless skin cleaner and then wash with warm soap and water. If irritation occurs, get medical attention.

Ingestion: Do not induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Most important symptoms/effects, acute and delayed: Itching. Rashes. Serious eye irritation or damage.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5. **Fire Fighting Measures**

Extinguishing Media: Carbon dioxide, foam, dry chemical, water fog.

Special Fire Fighting Procedures: Wear complete firefighting gear and self-contained breathing apparatus to protect against potential harmful and/or irritating fumes. Use water to keep fire exposed containers cool. Do not use high volume water jet on the fire as this may spread the area of the fire.

Special Protective Equipment for Fire-fighters: Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.

Unusual Fire and Explosion Hazard: Closed containers exposed to extreme heat may rupture.

Hazardous Decomposition Materials (Under Fire Conditions): Combustion products may include, but are not limited to: phenolics, carbon monoxide, carbon dioxide.

Section 6. **Accidental Release Measures**

Personal Precautions, Protective Equipment and Emergency Procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the involved area. Avoid contact with eyes, skin and clothing. Use gloves and safety glasses. Prevent contamination of soil and water.

Cleanup and Disposal of Spill: Stop leak without additional risk. Dike and absorb with inert absorbent material (e.g., sand) and collect in a suitable, closed and labeled container. Wash the spill area with water and detergent. Dispose of in accordance with applicable local and federal environmental control regulations.

Section 7. Handling and Storage

Precautions for Safe Handling: Ventilate work area. Avoid skin contact. Skin contact with hot material may cause thermal burns. Wash skin thoroughly after handling. Launder contaminated clothing before reuse or discard. Never apply a direct flame to any container of product.

Conditions for safe storage including any incompatibilities: Store in a cool, dry place with adequate ventilation. Keep in original containers. Store in tightly closed containers to prevent moisture absorption and loss of volatiles. Store away from heat and open flame.



CONTOUR APEX PART A FILLER

Section 8. Exposure Controls / Personal Protection

Exposure Guidelines:

Component	Exposure Limits		
Component	ACGIH-TLV (TWA)	NIOSH	OSHA-PELs
Calcium metasilicate	10 mg/m ³ - 8h Inhalable fraction 3mg/m ³ – 8h (respirable fraction)	-	5mg/m³ (respirable fraction) 15mg/m³ (total dust)

Appropriate Engineering Controls: Ventilation must be adequate for most operations.

Personal Protective Equipment:

Respiratory Protection: In case of inadequate ventilation wear respiratory protection. Use respirators when exposure to vapors from heated material.

Eye / Face Protection: Wear safety glasses with side shields or chemical splash goggles when exposure is more likely.

Skin Protection: Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

Additional protective measures: Wash thoroughly after handling. Avoid breathing vapors from heated material. Protective skin cream barriers can be applied to hands in addition to gloves for added protection.

Section 9. Physical and Chemical Properties

Physical Appearance: Blue paste

Odor: Mild

Odor Threshold:

pH:

No data available

No data available

Flash Point: 218 °C

Melting Point Range:No applicableBoiling point:No data availableEvaporation rate (ether=1):No data availableFlammability (solid, gas):No data available

Flammability Limits in Air: Not established for this product

Viscosity: 534,000 cPs at 75 °F (Rheomether Method)

Water Solubility: Insoluble

Solubility in other solvents:

Vapor Pressure:

Vapor density (Air=1)

Relative Density:

Partition coefficient (n-octanol/water):

Auto-ignition Temperature:

No data available

Section 10. Stability and Reactivity

Reactivity: Stable

Chemical Stability: Stable under standard normal conditions.



CONTOUR APEX PART A FILLER

Possibility of Hazardous reactions: None under normal processing. Hazardous polymerization will not occur by itself.

Conditions to Avoid: To avoid thermal decomposition, do not overheat. Incompatible products.

Incompatible Materials / Chemicals: Acids. Bases. Strong acids. Strong oxidizing agents. Reacts with amines.

Hazardous Decomposition Products: Uncontrolled exothermic reaction of epoxy resin releases carbon monoxide, carbon dioxide, aldehydes.

Section 11. Toxicological Information

Numerical measures of toxicity:

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Bisphenol A – Epichlorohydrin polymer	>5,000 mg/kg (rat)	20,000 mg/kg (rabbit)	-
Phenol-formaldehyde polymer, glycidyl ether	>2,000 mg/kg (rat)	2,000 mg/kg (rabbit)	-

Information on the likely route of exposure:

Eye contact: May cause eye irritation. Corneal injury is unlikely.

Skin contact: Prolonged contact may cause skin irritation with local redness.

Inhalation: No known effect. **Ingestion:** No data available.

Symptoms related to the physical, chemical and toxicological characteristics: No data available Delayed and immediate effects and also chronic effects from short and long term exposure:

Short term exposure: No specific data. Long term exposure: No specific data

Section 12. Ecological Information

Ecotoxicity Effects:

Data for components:

Bisphenol A/epichlorohydrin epoxy resin

Acute LC50 (daphnia magna): 1.3 mg/L Acute LC50 (fathead minnow): 3.1 mg/L

Phenol-formaldehyde polymer, glycidyl ether

Acute EC50 (daphnia magna): 3.5 mg/L Acute LC50 (Leuciscus idus): 5.7 mg/L

Propane 2,2 bis[p-2,3 epoxypropoxy)phenyl]-polymers: Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

Fish Acute & Prolonged toxicity: For similar material: LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96h: 2 mg/l

Aquatic Invertabrate Acute Toxicity: EC50, Daphnia (water flea), static test 48h, immobilization; 1.8 mg/l

Aquatic Plant Toxicity: ErC50, Scenedesmus capricornutum (fresh water algae), static test, Growth rate inhibition, 72h: 11mg/l

Toxicity to Microorganisms: IC50; bacteria, 18h: >42.6 mg/l



CONTOUR APEX PART A FILLER

Aquatic Invertebrate Chronic Toxicity Value: Daphnia magna (water flea), semi- static test, 21d, NOEC: 0.3mg/l.

Persistence and degradability:

Propane 2,2 bis[p-2,3 epoxypropoxy)phenyl]-polymers: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method	10 Day Window
12%	28d	OECD 302B Test	Not applicable

Bioaccumulative potential: Bioconcentration potential is moderate.

Mobility in soil: No information available.

Other adverse effects: No information available.

Section 13. Disposal Considerations

Waste treatment methods: Do not dump to ground, sewers or watercourses. Dispose of at a licensed waste disposal facility utilizing methods that are in compliance with all applicable federal, state and local laws regulations. Waste characterization and compliance with applicable laws are the responsibility solely of the waste generator.

Uncleaned packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport Information

DOT

Proper Shipping Name: Not regulated by DOT.

Technical shipping name:
UN-Number:
Hazard Class:
Packing Group:
Marine pollutant:
Not applicable
Not applicable
Not applicable

Section 15. Regulatory Information

SARA Title III Section 311/312 (40CFR370): Acute health hazard SARA Title III Section 313 (40CFR372): No reportable components CERCLA Status (40CFR302): No reportable quantity components

OSHA/NTP/IARC Carcinogen status: Not listed.

TSCA Status: All components are listed on TSCA Inventory or otherwise comply with TSCA requirements.

Canada WHMIS Classification: D2B

Chemicals known to the State of California to cause Cancer or Reproductive Toxicity: This product contains trace amounts of Epichlorohydrin CAS 106-89-8

Hazardous Products Act Information: This product contains the following ingredients which are Controlled Product and/or are on the Ingredient Disclosure List (Canadian HPA Section 13 and 14):

Propane 2,2 bis[p-2,3 epoxypropoxy)phenyl]-polymers, CAS#: 25085-99-8



CONTOUR APEX PART A FILLER

Section 16. Other Information

Key Legend Information:

N/A – Not Applicable
ND – Not Determined
OSHA – Occupational Safety and Health Administration
NIOSH – National Institute for Occupational Safety and Health

The information contained herein is based on the data available to us and is believed to be accurate. The data is offered in good faith as typical values and not as product specification. The information in this data sheet was compiled from information supplied by the vendors of the components of this compound. CSNRI makes no warranty either expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The recommended industrial hygiene and safe handling procedures are believed to be genuinely applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. CSNRI assumes no responsibility for injury from the use of the product described herein. The information is intended only to assist in the safe handling of this material. CSNRI DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR FREEDOM FROM PATENT INFRINGEMENT. CSNRI WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.