

PPR PART A RESIN

Section 1. Product and Company Identification

Product Name: PPR Part A Resin

Supplier: CSNRI | 621 Lockhaven Drive. Houston, TX 77073 | +1 281.590.8491

Emergency Phone Number: 800.424.9300 (CHEMTREC)

+1 703.741.5970 (Outside the US)

Product Description: Epoxy resin

Product Use: Intended to repair pipes

Section 2. Hazards Identification

Classification of the substance or mixture

Skin corrosion/irritation

Eye damage/irritation

Sensitization - Skin

Caregory 2

Category 2

Category 1

Category 1

Category 2

Category 2

Category 2

Category 2

Category 2

Category 2

Hazard pictograms:







Signal word: Warning Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.



PPR PART A RESIN

Other hazards: None known.

Section 3. Composition/Information on Ingredients

Substance/Mixture: Preparation **Chemical nature**: Epoxy constituents

Hazardous components:

Component	CAS#	% Composition	
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phe-nyleneoxymethylene)]bis-, homopolymer	25085-99-8	70 – 90	
phenol, 4, 4'-(1-methylethylidene)bis-,polymer with (chloromethyl)oxirane	25068-38-6	1 – 5	
Fatty acids, C18-unsatd., dimers, polymers with bisphenol A and epichlorohydrin	67989-52-0	1 – 5	
p-tert-butylphenyl 1-(2,3-epoxy)propyl ether	3101-60-8	1 – 5	
Oxirane, 2-[[3-(trimethoxysilyl)propoxy]methyl]-	2530-83-8	1 – 5	
Calcium Aluminium Borosilicate	65997-17-3	1 – 5	
Titanium Dioxide	13463-67-7	0.1 – 1	
carbon black	1333-86-4	0.1 – 1	

Section 4. First Aid Measures

First Aid Measures for Accidental:

General advice: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.

Inhalation: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Skin contact: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

Eye contact: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

Ingestion: Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

<u>Most important symptoms and effects, both acute and delayed:</u> Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.

Section 5. Fire-fighting Measures



PPR PART A RESIN

Suitable extinguishing media: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Use firefighting measures that suit the environment.

Unsuitable extinguishing media: High volume water jet.

Specific hazards during fire-fighting: Do not allow run-off from fire-fighting to enter drains or water courses. **Special protective equipment for fire-fighters:** Wear self-contained breathing apparatus for fire-fighting if necessary.

Further information: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment.

Environmental precautions: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and material for containment and cleaning up: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Section 7. Handling and Storage

Precautions for Safe Handling: Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Section 8. Exposure Controls/Personal Protection

Exposure Limits:

Component	Exposure Limits		
Component	ACGIH	OSHA PEL	NIOSH
Titanium dioxide	10 mg/m³ TWA	15 mg/m ³ TWA (total dust)	-
Carbon black	3 mg/m3 TWA (Inhalable fraction)	3.5 mg/m3	-

Appropriate Engineering Controls: Ventilation must be adequate for most operations.

Personal protection equipment:

Respiratory protection: In the case of vapour formation use a respirator with an approved filter.

Hand protection: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection: Eye wash bottle with pure water. Tightly fitting safety goggles. Wear face-shield and protective suit for abnormal processing problems.



PPR PART A RESIN

Skin and body protection: Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

Section 9. **Physical and Chemical Properties**

Physical state: Liquid

Color: No data available

Odor: Mild

Odor threshold: No data available **Melting point:** No data available Freezing point: No data available **Boiling point:** Not applicable Flammability (solid, gas): No data available Flash point: No data available **Auto-ignition temperature:** No data available **Decomposition temperature:** No data available No data available :Ha Viscosity, kinematic: No data available **Viscosity:** No data available Solubility: No data available Vapor pressure: No data available Density: No data available Relative vapor density at 20 °C: No data available No data available No data available No data available

Relative evaporation rate (butyl acetate=1): **Explosive properties:** Oxidizing properties: **Explosive limits:** No data available

Section 10. Stability and Reactivity

Reactivity: No decomposition if stored and applied as directed.

Chemical stability: No decomposition if stored and applied as directed.

Possibility of hazardous reactions: No decomposition if stored and applied as directed.

Conditions to avoid: No data available. **Incompatible materials:** No data available.

Hazardous decomposition products: No data available.

Section 11. Toxicological Information

Acute toxicity: Not classified based on available information.

Dermal: Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Oxirane, 2-[[3-(trimethoxysilyl)propoxy]methyl]-:

LD50 (rat): 8,030 mg/kg Oral: LD50 (rabbit): 4,248 mg/kg Dermal:

Skin corrosion/irritation: May cause skin irritation and/or dermatitis.



PPR PART A RESIN

Serious eye damage/irritation: Causes serious eye irritation. May cause irreversible eye damage.

Oxirane, 2-[[3-(trimethoxysilyl)propoxy]methyl]-:

Species: Rabbit

Result: Risk of serious damage to eyes.

Assessment: Risk of serious damage to eyes.

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information. **Germ cell mutagenicity:** Not classified based on available information.

Carcinogenicity: Suspected of causing cancer.

IARC Group 2B: Possibly carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7)

Carbon black (1333-86-4)

OSHANo component of this product present at levels greater than or equal to 0.1% is identified

as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified

as a known or anticipated carcinogen by NTP.

Reproductive Toxicity: Not classified based on available information. **STOT - single exposure**: Not classified based on available information. **STOT - repeated exposure:** Not classified based on available information.

Aspiration Toxicity: Not classified based on available information.

Section 12. Ecological Information

Ecotoxicity: Toxic to aquatic life with long lasting effects.

Oxirane, 2-[[3-(trimethoxysilyl)propoxy]methyl]-:

Toxicity to fish: LC50 (Cyprinus carpio (Carp)): 55 mg/l

Exposure time: 96 h

LC0 (Cyprinus carpio (Carp)): 30 mg/l

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 473 mg/l

Exposure time: 48 h

Toxicity to algae: EC50 (Desmodesmus subspicatus

(green algae)): 255 mg/l Exposure time: 72 h

Persistence and degradability: No additional information available.

Bioaccumulative potential:

Oxirane, 2-[[3-(trimethoxysilyl)propoxy]methyl]-: Partition coefficient: n-oc-tanol/water: log Pow: -

0.854

Mobility in soil: No additional information available.

Other adverse effects:

Ozone-Depletion Potential: Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances. Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82,



PPR PART A RESIN

Subpt. A, App.A + B). Additional ecological infor-mation: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

Section 13. Disposal Considerations

Disposal methods: Waste from residues: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Uncleaned packaging: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

Section 14. Transport Information

IATA-DGR

UN Number: UN 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Diglycidyl Ether

Resin) Class: 9

Packing group: III

Labels: Miscellaneous Dangerous Goods
Packing instruction (cargo aircraft): 964
Packing instruction (passenger aircraft): 964

IMDG-CODE

UN Number: UN 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Diglycidyl Ether

Resin)
Class: 9

Packing group: III

Labels: 9

EmS Code: F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable for product

as supplied.

National Regulations

49 CFR

UN Number: UN 3082

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Diglycidyl Ether

Resin) Class: 9

Packing group: III Labels: Class 9 ERG Code: 171

Section 15. Regulatory Information

EPCRA - Emergency Planning and Community Right - to - Know Act

CERCLA Reportable Quantity: This material does not contain any components with a CERCLA RQ.



PPR PART A RESIN

SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards: Chronic Health Hazard. Acute Health Hazard.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61). This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F). This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act: This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act, Section 311, Table 116.4A. This product does not contain any Hazardous Chemicals listed under the U.S. Clean Water Act, Section 311, Table 117.3. This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307.

California Prop 65: WARNING! This product contains a chemical known to the State of California to cause cancer.

Titanium Dioxide 13463-67-7 carbon black 1333-86-4

Section 16. Other Information

The information contained herein is based on the data available to us and is believed to be accurate. The data is offered in good faith as typical values and not as product specification. The information in this data sheet was compiled from information supplied by the vendors of the components of this compound. CSNRI makes no warranty either expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The recommended industrial hygiene and safe handling procedures are believed to be genuinely applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. CSNRI assumes no responsibility for injury from the use of the product described herein. The information is intended only to assist in the safe handling of this material. CSNRI DISCLAIMS ALL EXPRESS AND IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR FREEDOM FROM PATENT INFRINGEMENT. CSNRI WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Date of issue: 06/17/2013 **Revision date:** 12/12/2019 **Supersedes:** 05/17/2015 **Version:** 3.0